Produktdatenblatt

Delegierte Verordnung (EU) 2015/1186

Name oder Warenzeichen des Lieferanten	**Sabah**
Modellkennung	**PLT02**
Energieeffizienzklasse	**A+**
Direkte Wärmeleistung	**10,9 kW**
Indirekte Wärmeleistung	**- kW**
Energieeffizienzindex	**111**
Brennstoff-Energieeffizienz (bei Nennwärmeleistung)	**83,0 %**
Brennstoff-Energieeffizienz (bei Mindestlast)	**- %**
Besondere Vorkehrungen	**-**

EPREL-Eintragungsnummer 2693107

Das Modell wurde auf dem Unionsmarkt in Verkehr gebracht , und zwar ab dem 14/04/2026.

https://eprel.ec.europa.eu/qr/2693107

Freiwillige Parameter:

GTIN-Kennung: 9180018940046

Lieferant: RINNEXA e.U. (Importeur)

Website: www.rinnexa.at

Kundenbetreuung:

Name: Rinnexa

Website: www.rinnexa.at

E-Mail-Adresse: kontakt@rinnexa.at

Telefonnummer: 069911169244

Anschrift:
Schloßgasse I. 43
2512 Tribuswinkel
Österreich

Sabah

No : 17

DECLARATION OF PERFORMANCE ACCORDING TO REGULATION (EU) 305/2011

1. Unique identification code of the product-type	Pellet Cooking Stove
2. Model and/or serial number	PLT02
3. Intended uses of the product in accordance with harmonised technical specification	Cooker for domestic heating, fuelled with wood pellet, without hot water production.
4. Name or registered trade mark of the manufacturer	SABAH Emaye Soba Sanayi Ltd. Sti. Aksehir Organize Sanayi Bölgesi 4. Sk. No: 10 Aksehir/Konya Tel : +90 332 8111108 info@sabahsobalari.com.tr
5. System of assessment and verification of constancy of performance of the construction product.	System 3
6. Harmonized technical specification	EN 16510-1:2022, EN 16510-2- 5:2022
7. Notified laboratory	"ITEM Consult" Ltd. № CPR 21 - NB 1837
8. Test report number (type testing under System 3)	CPR 509A/16.12.2025
9. Date of test report	16.12.2025
10.Declared performance	
Fire safety	Pass
Safety distance from combustible materials	Minimun distances, in mm Rear 500 Side 800 Front 800
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Cleanability	Pass
Maximum operating pressure	-
Mechanical resistance (to carry a chimney/flue)	NPD (no performance determined)
Flue gas temperature at nominal heat output	248,9˚C
Emission of combustion products	CO: 277 mg/m³ NOx: 186 mg/m³ OGC: 11 mg/m³ PM: 18 mg/m³
Thermal output and Energy efficiency	Pass
Nominal heat output Room heating output	10,9 kW 10,9 kW
Energy efficiency at nominal heat output	83 %
11. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 10.	
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	
Place and Date of Issue Aksehir / 02.02.2026	Manufacturer Managing Director Mehmet Emin Koyuncu Sabah Emaye Soba Day. Tük. Malları İnş. Taah. Müteahhitlik Nak. San. ve Tic. Ltd. Şti. Akşehir O.S.B. Reis Mah. 4. Sk. No:10 Akşehir/KONYA Tel : 0 332 821 11 09 Fax : 0 332 821 11 25 Akşehir V.D. : 736 044 48 14 Tic. Sic. No : 4072


Sabah® EMAYE SOBA SANAYİ LTD. ŞTİ. Akşehir Org. San. Bbl. 4. Sk. No:10 AKŞEHİR/KONYA/TÜRKİYE	CE 26
MODELL: PLT02 EN 16510-1:2022, EN 16510-2-5:2022 Raumheizer für Pelletbrennstoffe in Gebäuden ohne Heiz- und Brauchwassererwärmung	MODEL: PLT02 Pellet Cooking Stove EN 16510-1:2022, EN 16510-2-5 :2022 Ecodesign 2022 Household Cookers Working on Pellet Fuel
Prüfstelle: NB 1837 / Prüfbericht: Nº CPR 509A/16.12.2025	Approved by : NB1837 / Report № CPR 509A/16.12.2025
DoP-Nummer:17	Dop - Number : 17
Brandsicherheit: erfüllt	Fire Safety : Pass
Brandverhalten: A1	Reaction to Fire : A1
Oberflächentemperatur: erfüllt	Surface temperature : Pass
Emission von Verbrennungsprodukten bez.auf 13 % O2: erfüllt / CO-Emission: 277mg/m³	Emission of combustion products at 13% O2 Pass / CO Emission : 277mg/m³
Staub-Eimission: 18mg/m³/NOx:186mg/m³	Dust Emission:18mg/m³/NOx:186mg/m³
OGC: 11mg/m³	OGC: 11mg/m³
Wärmeleistung / Energieeffizienz: erfüllt	Thermal output and Energy efficiency:Pass
Nennwärmeleistung: 10,9kW	Nominal heat output : 10,9kW
Wirkungsgrad: n [83%]	Energy efficiency : 83%
Abgastemperatur: 248,90°C	Flue gas temperature : 248,90°C
Abgasmassenstrom: 9,1 g/s	Exhaust gas mass flow rate : 9,1g/s
Mindestförderdruck: 12 Pa	Flue gases draught : 12 Pa
Zugelassene Brennstoffe: Holzpellets nach	Fuel Type : Wood Pellet EN ISO 17225-2
Abstand zu brennbaren Bauteilen: hinten min. 50 cm / Seite min. 80 cm / vorn min. 80 cm	Min. distance to combustible materials : Rear: 50cm / Side: 80cm / Front: 80cm
Lesen und befolgen Sie die Bedienungsanleitung. Nur zugelassene Brennstoffe verwenden.	Follow user's instructions. Use only recommended fuels.
MADE IN TURKEY	

ENERG
енергия · ενεργεια
Y IJA IE IA

Sabah **PLT02**



A+



10,9
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186